

CM Pro

The ultimate all-in-one
powerful commercial display

The CM Pro is flexible and versatile with inbuilt CleverLive
digital signage for broadcasting information.

Available in a range of sizes

43" 4K | 50" 4K | 55" 4K

65" 4K | 75" 4K | 98" 4K



Scan the QR Code
to book your flu jab



Let's help keep everyone healthy
Scan the QR code or speak to a staff member





HI, HELLO, BONJOUR
**WELCOME TO
ELMWOOD GROVE**



Powered by
CleverLive

Enter the building through the main entrance.
Walk straight along the corridor and the coffee shop is ahead.



Welcome

Scan the QR Code to check-in.

Please take a seat, a colleague will
be with you soon.



**Screen
Sustainability
Scheduling**

for reduced power
consumption

CLEVER® LIVE

Subscription free feature rich digital signage.

Create your account today at **cleverlive.com**

1-year MDM* included

Remote access to manage, view and support your
display for the ultimate in control and flexibility.

Key Features




Ultra HD
Resolution



Vibrant Picture
Quality



16/7 Operation



Landscape &
Portrait



One Touch
Messaging &
Broadcasting



Screen
Sustainability
Scheduling
Power
Management



Control
Integration



Digital Signage
Full Screen
Posters + Videos



Android
Technology




MDM Built-in
Management
Control



OTA Updates &
Cloud Accounts



Upgrade your solution




Add a **PICO XL** or **PRO V4** media player for multizoned digital signage, or add an **OPS** or **Video Conferencing Bar** to create a Microsoft Teams Room or Zoom Room environment.



partnered with

logitech



CM Pro Specifications

Panel

Screen size	43" 50" 55" 65" 75" 98"
Backlight Type	D-DLED
Panel Type	IPS
Brightness (Typical)	43", 50", 55", 65", 75", 98" 500 cd/m2
Native Resolution	3840 x 2160 (UHD)
Contrast Ratio (Typical)	1200:1
Dynamic Contrast	43", 50", 55", 65", 75" 50000:1 98" 40000:1
Panel Lifetime (Minimum)	43", 50", 55", 65", 75" 50,000Hr 98" 30,000Hr
Response Time (Typical)	8 ms
Viewing Angle	178 Vertical, 178 Horizontal
Colour Value	1.07B (8-Bit + FRC)
Screen Treatment	3H
Haze Level	1%
Refresh Rate	60Hz
Orientation	43", 50", 55", 65", 75" Landscape and Portrait 98" Landscape
Operation Hours	16/7
Area of Usage	Indoor

Mainboard

Android Option	400vs: Android 9.0
Android CPU	4xCA55
Android GPU	MaliG31mp2
Android RAM	2GB DDR4- 2666Mhz
Android Storage	16GB eMMC
Scan Rate	200Hz

Connectivity

HDMI-In	4xHDMI2.0
HDMI-Out	x1
USB2.0	x1
USB3.0	x1
Internal USB	x1
OPS/SDM	x1
Audio In	Line In L/R
Audio Out	Headphone, SPDIF
Micro SD	x1
RS232	3.5mm Jack
LAN	10/100/1000 Mbps
WiFi	2.4GHz and 5GHz
RJ12	For Service

Power

Supply	110v AC - 240v AC 50/60Hz
Power Consumption (Typical)	43" 127 (W) Typical/160 (W) Max 50" 121 (W) Typical/160 (W) Max 55" 138 (W) Typical/180 (W) Max 65" 194 (W) Typical/220 (W) Max 75" 235 (W) Typical/320 (W) Max 98" 550 (W)
Deep Standby	≤0.5 W

Mechanical

Product Dimensions	43" 963 x 83 x 555mm 50" 1121 x 83 x 646mm 55" 1236 x 83 x 709mm 65" 1456 x 96 x 834mm 75" 1684 x 100 x 967mm 98" 2225 x 98.6 x 1282 mm
Packaging Dimensions	43" 1050 x 178 x 718mm 50" 1215 x 165 x 775mm 55" 1369 x 165 x 874mm 65" 1650 x 190 x 997mm 75" 1948 x 210 x 1170mm 98" 2423 x 380 x 1563 mm
Product Weight	43" 10.5kg 50" 13.7kg 55" 18.1kg 65" 24.4kg 75" 38.1kg 98" 102.2Kg
Packed Weight	43" 14.3kg 50" 18.3kg 55" 23.3kg 65" 31.3kg 75" 51.2kg 98" 126.6Kg
VESA Mounting	43" 50" 200mm (W) x 200mm (H) M6 55" 400mm (W) x 400mm (H) M6 65" 600mm (W) x 400mm (H) M6 75" 600mm (W) x 400mm (H) - M6 98" 1000 x 400 mm - M6
Bezel Width	43" 6/6/6/9mm 50" 9/9/9/13mm 55" 9/9/9/11mm 65" 10/10/10/14mm 75" 21/16/16mm 98" 25mm

CM Pro Specifications

Features

Main	Built in Digital Signage playback with alert auto source switching, Remote MDM (* MDM designed for remote support and app updating), Power Scheduler, Active Standby (HDMI Wakeup) , HDMI CEC, USB Autoplay, Panel Lock, Pixel Shift, External Control, Real Time Clock (RTC)
Mechanical	Joystick Control, IR sensor Cable, OPS module slot, Secure USB cover, Detachable Power Cable
Speaker	43" 2x8 W 50" 55" 65" 75" 2x10 W 98" 2x12 W

Environmental Conditions

Operating Temperature	0-40 C
Operating Humidity	10-90%

Accessory

Standard	QSG, Power cable, IR extender cable, Remote Control, 2 x AAA Battery
----------	--

Installation

The installation of this product should be completed by a qualified installer. Use of components not supplied by Clevertouch or not meeting minimum specifications may impact performance, safety and warranty. For more information, visit clevertouch.com

Warranty

Warranty term and upgrade options vary by region. Contact your local reseller or distributor for information and visit clevertouch.com/about/warranty

Compliance & Certification

Regulatory Certification	
--------------------------	---

Support

For all Clevertouch products, visit: support.clevertouch.com

Statement

Size and weight vary by configuration and manufacturing process, please refer to the actual product. The product images are for illustrative purposes only and may slightly differ in appearance, colour, size, etc. from the actual product. The description, illustrations, etc. in this document may subject to change in accordance with the latest product specification and performance. Should the above-mentioned change in the document become necessary, the document may be updated without written notice.

© 2021 Clevertouch. All rights reserved. Sahara Presentations Systems PLC. is part of the Boxlight group of companies, and the owner of trademarks in several global jurisdictions including but not limited to Clevertouch, the Clevertouch logo, UX Pro, IMPACT™, IMPACT Plus™, Impact MAX, CleverLive, LUX, Lynx, CleverMessage, Cleverstore and Clevershare. All third-party trademarks (including logos and icons) referenced by Clevertouch remain the property of their respective owners. Unless specifically identified as such, Clevertouch's use of third-party trademarks does not indicate any relationship, sponsorship, or endorsement between Clevertouch and the owners of these trademarks. Applicable Terms and Conditions for warranty and support available at clevertouch.com/about/warranty. All weights and dimensions are approximate. Product specifications are subject to change without notice. Clevertouch.com.