

Mimio DS Series 43"

Product# DS430



The Mimio DS Series delivers powerful brilliance with effortless control. This large format professional display is a complete digital signage solution and sized perfectly to fit any classroom, hallway, meeting room, or office space.

Product Features

- Ultra-narrow edge metallic appearance
- 4K Ultra HD display
- AI PQ Scene Recognition
- Portrait and Landscape
- Screen Splicing
- Support wireless screen-sharing
- Support the network wake-up function
- Support serial command
- Support dual network port
- Wall hanging / scaffolding can be adapted to various installation requirements
- Large memory and storage of 3G/32G

Display Specifications	
Size Options	43"
Panel Type	VA
Response Time	6.5ms
Aspect Ratio	16:9
Display Area (HxV)	941.184 x 529.416mm
Pixel Pitch (HxV)	0.2451 × 0.2451mm
Resolution (HxV)	3840 x 2160
Refreshing Frequency	60Hz
Display Color	1.07B (10bit)
NTSC	72%
Contrast Ratio	5000:1
Viewing Angle	178°
Back Light Unit	DLED
Brightness with glass (min)	400cd/m ²
Brightness with glass (typ)	450cd/m ² (White Balance Adjusted)
Back Light Lifetime	≥50000 Hours
Picture in Picture	Yes
Install Mode	Wall Mounting / Mobile Stand

Operating System	
System Version	Android 11.00
RAM	4GB
ROM	32GB
CPU	A55*4
GPU	MaliG52 MP2
Audio	
Sound Channel	2.0
Speaker Power	2 × 10W
Sound Pressure Level	81dB
Peak Power	54W
Power	
Power Requirements	100-240V~ 50/60Hz 2.5A
Overall Power (Max.)	250W
Typical Power* [1]	110W
Standby Power	≤0.5W
i/o Port	
HDMI IN (2 Ports)	Up to 4K@60Hz, HDCP 2.1, CEC, ARC (HDMI 1)
HDMI Out	1 (HDMI Daisy chain, up to 3*3) Follow HDMI IN; Android channel do not support
USB 2.0 (1 Port)	For system upgrades
USB 3.0 (1 Port)	External U disk, mouse, and other peripherals



by Boxlight®

USB Type-C (1 Port)	Video, Audio, External Type-C U disk
Audio Out (1 Port)	3.5mm Phone Jack
SPDIF (1 Port)	PCM Output Format
RS232 (1 Port)	Baud Rate 9600
LAN RJ45 IN (1 Port)	10M/100M/1000Mbps
Physical Specifications	
Dimension (L×H×D)	1463.3 × 838 × 81.6mm
Dimension (package) L×W×H	1056×156×672mm
Thickness of machine & wall mount	95.4mm (WIB9080A)
Wall-hanging Screw Spec	M6 × 12mm
VESA	200 × 200mm
Net Weight (kg) Weigh (lbs)	9.90 21.83
Gross Weight (kg) Weigh (lbs)	13.85 30.53
OPS Slot	No
Accessories	
Power Cord	1
Remote Control	1
Batteries for Remote	2

Environmental Conditions	
Operation Temperature	0°C~40°C
Operation Humidity	10%~90%RH
Storage Temperature	-20°C~60°C
Storage Humidity	10%~90%RH
Altitude	Below 5000 meters
Standard Module	
Wireless Module	MP4-WIFI-MOD

Statement

Size and weight vary by configuration and manufacturing process, please refer to the actual product.

The product images are for illustrative purposes only and may slightly differ in appearance, color, size, etc. from the actual product. The description, illustrations, etc. in this document may subject to change in accordance with the latest product specification and performance. Should the above-mentioned change in the document become necessary, the document may be updated without written notice.